



Posts

Profile posts, polyester coated on galvanized with fixing system to be used with all Nylofor panels.



Bekafix® posts

Profile

- Tubular post, profiled in "H" shape
- With side sleeve on the left and the right
- With 3 pre-drilled holes for fixing of the special metal security clips with bolts
- With punched holes for positioning and fixing of the panels by means of fixing clips
- Cross section of the post: 70 x 44 mm
- Interior measure of the sleeve: 43 mm
- Plate thickness: < 2475 mm: 1,25 mm
≥ 2475 mm: 1,50 mm
- I/V: 6,48 cm³

Coating technique

Galvanised: inside and outside and polyester coated (minimum 60 microns)



Accessories

- Security fixation system: plastic coated metal clip with as an option stainless bolt with nut with break-off head
- Metal or polyamide fixing brackets
- Bekafix installation tongs
- Floor plate
- Connection piece to create bent arm for panels
- Single or double upstand for Bekafix posts



Colours (p 116)

Green RAL 6005, White RAL 9010 - Other colours: on request.

BEKAFIX POSTS

Post length mm	Number of fixings per intermediate and corner posts	Number of fixings per end post
1075	2x2	1x2
1475	2x2	1x2
1675	2x2	1x2
1975	2x3	1x3
2175	2x3	1x3
2475	2x4	1x4
2575	2x4	1x4
3175	2x4	1x4

Applications

- For Nylofor Panels

