


Posts

Professional round metal posts, galvanised and plastic coated.



Round posts



Round tubular posts with holes every 49,5 cm for fixing the wire holders (wire holders to be ordered separately) with cap

Coating technique

Galvanised in-and outside (275 g/m² - both sides combined) and plastic coated (min. 60 micron)



Accessories

Designed to all situations

Colours (p. 116)

Green 6005, some types also in black 9005

ROUND POSTS* (CORNER AND INTERMEDIATE POSTS)								
Post diameter (mm)	Ø 32	Ø 38	Ø 38	Ø 42	Ø 48	Ø 48	Ø 60	Ø 76
Plate thickness (mm)	1,25	1,25	1,5	1,5	1,25	1,5	2	2
Post length (mm)								
1200	•		•					
1500	•		•					
1750		•			•			
2100				•		•**		
2200							•**	
2400						•**		
2500							•**	
2600						•**		
2700							•**	

* Round tubular posts, with 1 wire holder and cap with Betafence logo ** also in black RAL 9005

ROUND PROFESSIONAL POSTS								
3100						•		
3250							•	
3500						•	•	
3750						•	•	•
4750							•	•
6000							•	

Round tubular posts with holes every 49,5 cm for fixing the wire holders (wire holders to be ordered separately) with cap

ROUND POSTS WITH BENT ARM								
3100						•		
3250							•	
3600						•	•	

Bent arm: length 45 cm, bent under a corner of 40°, with 3 holes for wire holders, with cap. Vertical part with inserts every 49,5 cm for wire holders and tension wires.

BRACE POSTS FOR BEKA CLIP AND ROUND POSTS								
1200	•							
1400	•							
1750			•					
2200			•**					
2700			•**					
3000			•			•		
3500						•		
4000						•		
4750						•		

** also in black RAL 9005 - Corner of the brace posts: 35° (Ø 38) - 47° (Ø 48) - Complete with fixing bolt for fixing to the brace and corner posts.

Applications

- For all fences on rolls

